



## RAIL MOUNTED M203

For the first time the M203 2003 system offers a grenade launcher with an integrated Picatinny rail fitting. The M203 2003 is based on the proven design of the standard M203, uniquely fitted with Picatinny rail interface mounts. These allow the launcher to be fitted to virtually any modern rifle or carbine by attachment of a suitable rail adaptor. While the launcher can be easily attached or removed in seconds, the clamping plates and recoil lugs ensure that the launcher is securely engaged into the weapon's rail mount.



## STANDARD M203

The M203 40mm Grenade Launcher as supplied by Lewis Machine & Tool Company to the United States Military. The launcher attaches under the barrel and forward of the magazine; the rifle magazine functions as a handgrip when firing. This model is intended to be used as close fire support for point and group area targets.



## PISTOL M203

A Lewis Machine & Tool Company exclusive option...the Pistol M203 Grenade Launcher, also 40mm. In lieu of carrying a weapon, or if your specific mission does not require or allow a complete weapon, we will offer the Pistol Grenade Launcher as an option. Compact and easily concealable, yet capable of the same impact as a standard or rail mounted M203.

## STANDARD M203

9 INCHES

12 INCHES

## RAIL-MOUNTED M203

9 INCHES

12 INCHES

## PISTOL M203

9 INCHES

12 INCHES

MODEL:	LMP300EL380	LMP300L360	L2B	L2D	L2BPG	L2CPG
CALIBER:	40 mm		40 mm		40 mm	
OPERATION:	Single Shot / Breech Loading		Single Shot / Breech Loading		Single Shot / Breech Loading	
BARREL LENGTH:	9" / 229 mm	12" / 305 mm	9" / 229 mm	12" / 305 mm	9" / 229 mm	12" / 305 mm
OVERALL LENGTH:	12.5" / 318 mm (closed) 17.5" / 444 mm (open)	15" / 381 mm (closed) 20.5" / 521 mm (open)	12.5" / 318 mm (closed) 17.75" / 451 mm (open)	15.25" / 387 mm (closed) 20.75" / 527 mm (open)	16" / 406 mm (closed) 21.5" / 546 mm (open)	19" / 486 mm (closed) 24.25" / 616 mm (open)
BREECH OPENING:	5" / 127 mm	5" / 127 mm	5.375" / 137 mm	5.375" / 137 mm	5.375" / 137 mm	5.375" / 137 mm
WEIGHT (EMPTY):	2.47 lbs / 1.1 kg	2.66 lbs / 1.2 kg	2.2 lbs / 1 kg	2.38 lbs / 1.1 kg	2.97 lbs / 1.4 kg	3.15 lbs / 1.4 kg
FINISH:	Mil-Spec Anodized Aluminum, and Manganese Phosphate Steel		Mil-Spec Anodized Aluminum, and Manganese Phosphate Steel		Mil-Spec Anodized Aluminum, and Manganese Phosphate Steel	
RIFLING:	1:48" / 1,219 mm RH Twist / 6 Land & Groove		1:48" / 1,219 mm RH Twist / 6 Land & Groove		1:48" / 1,219 mm RH Twist / 6 Land & Groove	
FIRE CONTROL:	Fire / Safe Switch		Fire / Safe Switch		Fire / Safe Switch	
RATE OF FIRE:	Operator Controlled		Operator Controlled		Operator Controlled	
MAX EFFECTIVE RANGE:	437 yd / 400 m		437 yd / 400 m		437 yd / 400 m	
SIGHTS:	Uses M203 leaf sights, quad sights, reflex sights and night sights.		Uses M203 leaf sights, quad sights, reflex sights and night sights.		Uses any rail mounting M203 optic or rail mounting iron sights.	
AMMO:	All military issue munitions as well as the longer less lethal munitions common in law enforcement and security use.		All military issue munitions as well as the longer less lethal munitions common in law enforcement and security use.		All military issue munitions as well as the longer less lethal munitions common in law enforcement and security use.	
SPECIAL NOTES:	Handguard mounting kits available for both carbine and rifle length weapons.		The M203 2003 Rail Mounted Grenade Launcher will fit 1913 Picatinny rails on virtually any tactical grip modern rifle or carbine by attachment of a suitable rail adapter		Features quick detach sling points for user preference set-up. Tactical pistol grip for comfort. 10.25" / 260.35 mm top Mil Std 1913 STANAG 4694 compliant rail space for optics & accessories. Makes issue rifle lighter but leaves user the M203 option. Easily slung.	

100% U.S. MADE

ISO 9001:2008 Registered  
LMTDEFENSE.COM

